## Architectural

## 906PT

## Mortice Deadlocking Escape Lock



Application:	<ul> <li>Non reversible latchbolt, please specify left or right handed when ordering</li> </ul>	
Specification:	<ul> <li>Modular case range</li> <li>European style casing with 72mm centres which accommodates most euro profile cylinders</li> <li>Pierced to accept bolt through furniture and security rose</li> <li>Anti-thrust bolt - deadlocks latchbolt when door is closed</li> <li>Split follower fitted with split spindle withdraws both latchbolt and deadbolt from the inside</li> <li>Available with radiused forend and strike upon request</li> <li>Case Size: 86mm</li> <li>Backset: 55mm</li> <li>Case: Galvanised Zinc</li> <li>Outer Forend: See finishes below</li> <li>Striking Plate: Finished to match outer forend</li> <li>Deadbolt: Stainless steel, 20mm single throw</li> <li>Latch Bolt: Stainless steel, 8mm</li> <li>Cylinder Type: Euro profile (not supplied)</li> <li>Available in SS, PS, PVD, AB and SB finishes</li> </ul>	Standa • Test
Finish:	<ul> <li>SS - Stainless Steel finish</li> <li>PS - Polished Stainless Steel finish</li> <li>PVD - Polished Brass finish</li> <li>AB - Antique Brass finish</li> <li>SB - Satin Brass finish</li> </ul>	• BS F resi: No
Technical Design:		63 235



ards:

- ted to BS EN 179 : 2008 7 6 B 1 3 4 2 A B
- EN 1634 Part 1 : 2000 4 hour fire istance Warrington Fire Test Certificate 145690



