

Door Closers

CE25T

Export Template 2/3/4/5 Rack & Pinion door closer



Application:

A template 2/3/4/5 rack and pinion closer for use on timber fire doors up to 1250mm wide.

Specification:

- A CE Marked and Certifire approved size 2/3/4/5 rack and pinion closer where size of closing force is determined by position on door face
- Tested for use in regular (fig 1), transom (fig 61) or parallel arm position (fig 66) for complete peace of mind
- Boxed product includes silver body, silver armset, all fixings and installation template/instructions for quick and easy install on site
- Non handed unit minimises stock holding
- Armset is adjustable to suit different frame details
- Parallel arm brackets supplied separately to minimise waste on site
- Closing speed valve can be adjusted on site to regulate time to shut each door
- Adjustable latching speed (final 15° of closing sweep) to ensure each door secures into the frame, regardless of lock or seal detail
- Backcheck control (adjustable after 75°) to protect nearby walls or users from door opening too quickly
- Approved for use on timber fire doors up to FD120
- Max opening angle of 180° on size 2/3/4 or 125° as size 5
- UNION branded silver trim plate supplied as standard - stainless steel version sold as an accessory






Standards:

- Certifire approved
- Tested to EN 1154 in all 3 mounting positions

3	8	2/3/4/5	1	1	4
---	---	---------	---	---	---

Finish:

- Silver as standard
- Stainless steel trim plates available as accessory



Door Closers

CE25T

Export Template 2/3/4/5 Rack & Pinion door closer



ASSA ABLOY

Variants:

Code	Description
X-CE25T-SIL	UNION R&P EN 2/3/4/5 closer w/o PA Bracket SIL
X-CE25T-PA-BRKT-SIL	Parallel arm bracket for CE25T SIL (supplied in 10s)
X-CE25T-TRIM-SS	UNION Trim Plate for CE25T Stainless Steel (supplied in 10s)

Door Closers

CE25T

Export Template 2/3/4/5 Rack & Pinion door closer



Application:

A template 2/3/4/5 rack and pinion closer for use on timber fire doors up to 1250mm wide.

Specification:

- A CE Marked and Certifire approved size 2/3/4/5 rack and pinion closer where size of closing force is determined by position on door face
- Tested for use in regular (fig 1), transom (fig 61) or parallel arm position (fig 66) for complete peace of mind
- Boxed product includes silver body, silver armset, all fixings and installation template/instructions for quick and easy install on site
- Non handed unit minimises stock holding
- Armset is adjustable to suit different frame details
- Parallel arm brackets supplied separately to minimise waste on site
- Closing speed valve can be adjusted on site to regulate time to shut each door
- Adjustable latching speed (final 15° of closing sweep) to ensure each door secures into the frame, regardless of lock or seal detail
- Backcheck control (adjustable after 75°) to protect nearby walls or users from door opening too quickly
- Approved for use on timber fire doors up to FD120
- Max opening angle of 180° on size 2/3/4 or 125° as size 5
- UNION branded silver trim plate supplied as standard - stainless steel version sold as an accessory






Standards:

- Certifire approved
- Tested to EN 1154 in all 3 mounting positions

3	8	2/3/4/5	1	1	4
---	---	---------	---	---	---

Finish:

- Silver as standard
- Stainless steel trim plates available as accessory



Door Closers

CE25T

Export Template 2/3/4/5 Rack & Pinion door closer



ASSA ABLOY

Variants:

Code	Description
X-CE25T-SIL	UNION R&P EN 2/3/4/5 closer w/o PA Bracket SIL
X-CE25T-PA-BRKT-SIL	Parallel arm bracket for CE25T SIL (supplied in 10s)
X-CE25T-TRIM-SS	UNION Trim Plate for CE25T Stainless Steel (supplied in 10s)