

MEDIATOR® lock, tubular frame version



Product description

The MEDIATOR® lock in its tubular frame version is available with different backsets and a comprehensive range of accessories.

Overview of Advantages

- Automatic locking system: Bolt and latch are blocked, therefore higher level of security
- Mechanical follow up control between double action latch and control latch
- Integrated panic function via internal door handle
- Changeover function for unlocking with a key from the outside
- Minimum rear backset for tubular frame design: 15 mm

Scope of delivery

- 1 lock
- 1 reducer

Note

- MEDIATOR® locks have a bolt through the handle and thus require front door furniture (inside handle or panic push bar, outside knob or push bar).

Accessories/Individual parts

- Distance plate 300 x 24 x 3 mm (Order number: Z09-DBRR3-----00)
- Spacer plate 300 x 24 x 5 mm (Order number: Z09-DBRR5-----00)
- Sliding part 100 x 30 x 3 mm (Order number: 65.000010)
- Standard profile cylinder cover For security fitting N44/N49 for standard profile cylinder (Order number: N5021X100000000)

Technical data

Backset	35 mm
Distance	92 mm
Type of cylinder	Euro profile cylinder
Bolt throw	20 mm
Handle follower	9 mm
VdS-approval	G 109 032, M 109314, Z 109001
Approval DIN EN 179	Certificate of Constancy of performance 0432-CPR-00007-11
DIN EN 1125 approval	Certificate of Constancy of performance 0432-CPR-00007-12
Building authorities test certificate	P-120003555
Mech. strength (EN 12209:2004)	200,000 cycles, 50N load on latch, Class 6 protection
Width face plate	24 mm
Face plate shape	square, flat
DIN direction	universal

Article number	609-202PZ-----1
EAN	4042203344686

