


SYSTEM-36/15 PLUS

U-SHAPED GASKETS


System-36/15 PLUS is a flexible U-shaped glazing gasket designed for 60 minutes fire resistance in doors and screens. Flexible enough to be fitted to curved corners and circular vision panels. Tested with many popular glass types. Supplied coiled in a box so it's easily dispensed and cut to length, reducing wastage.



FIRE RESISTANT GLAZING SYSTEMS




▲ SYSTEM-36/15 PLUS



▲ LG1721

For 54mm thick doors or rebated screen frames. Timber bead for 44mm thick FD30 doors also available



▲ LG1720

For unrebated screen frames.



SYSTEM SPECIFICATIONS

Test evidence

- ▶ Fire: BS EN 1634-1: 2014.
- ▶ Fire: BS 476-22: 1987.

Performance

- ▶ Provides 60 minutes fire resistance.

Size

- ▶ 22mm x 20mm.

Standard lengths

- ▶ 30m coils.

Seal material

- ▶ Intumescent graphite.

Finish

- ▶ Black with orange identification spine.

Glass thickness

- ▶ Suitable for use with 14mm - 16mm fire rated glass.

Glass type

- ▶ Please refer to Certifire certificate CF5060 for the full range of glass types.

Application

- ▶ Doors and screens.
- ▶ FD30 + FD60 fire doors.

Sodium silicate intumescent liner

- ▶ Liner is required for flaxboard substrates below 500kg/m³.

Glazing beads

- ▶ Glazing beads are required on both sides of the glass.
- ▶ Note: Hardwood or softwood beads are available (min density 550kg/m³).
- ▶ Fixing of beads: Screwed using No.8 x 45mm countersunk screws at 200mm nom. centres.

Accreditation

